



CARAWAY™

CARAWAY
TRUCK & BUS TIRES CATALOG

2020 v1.0



CARAWAY™

CW997

- Exceptional handling and side-skidding-resistant-performance
- Good wear-resistant capability; low heat generation in shoulders adaptive to high-speed and long-distance travel



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
11R24.5	16	149/146	M	14.5	8.25	3250	3000	830	1104	279
295/75R22.5	16	146/143	M	15	9	3000	2725	830	1014	298
11R22.5	16	146/143	M	14.5	8.25	3000	2725	830	1054	279



CARAWAY™

CW998

- Suitable for good road surface application.
- With excellent anti-side-skid character, low rolling resistance.
- Low heat generating, excellent high-speed driving character.



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
11R24.5	16	149/146	M	21.5	8.25	3250	3000	830	1116	279
295/75R22.5	16	146/143	M	21.5	9	3000	2725	830	1014	298
11R22.5	16	146/143	M	21.5	8.25	3000	2725	830	1059	279



CARAWAY™

CW176

- Sound water-evacuation and skidding-resistance capability
- Soundly resistance irregular wear



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
11R22.5	16	148/145	L	14.5	8.25	3150	2900	830	1045	292
12R22.5	18	152/149	M	15.5	9	3550	3250	930	1085	300
315/80R22.5	20	157/154	L	17	9	4125	3750	900	1076	312



CARAWAY™

CW981

- Extraordinary roadholding and tractive capability due to mixed pattern design
- Long original mileage and sound wear-resistant capacity



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
295/80R22.5	18	152/149	M	18	9	3550	3250	900	1050	298
315/80R22.5	20	157/154	L	19	9	4125	3750	900	1082	312



CARAWAY™

CW907

- Suitable to transport on asphalt road or other bad road condition
- Tyres with pattern have powerful grip ability, excellent traction character
- Good high-speed and anti-puncture character



● Recommend

● Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
11R22.5	16	146/143	M	17	8.25	3000	2725	830	1054	279
12R22.5	18	152/149	M	17	9	3550	3250	930	1085	300
315/80R22.5	20	157/154	K	20	9	4125	3750	900	1076	312
275/80R22.5	16	147/144	M	14	8.25	3075	2800	830	1012	276



CARAWAY™

CW158

- Sounds bearing, braking and driving capability



● Recommend

● Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
10.00R20	18	149/146	J	17	7.5	3250	3000	930	1054	278
11.00R20	18	152/149	K	17	8	3550	3250	930	1085	293
12.00R20	20	156/153	J	17.5	8.5	4000	3650	900	1125	315
12.00R24	20	160/157	J	17.5	8.5	4500	4125	900	1226	315
11R22.5	16	148/145	M	15	8.25	3150	2900	830	1045	292
12R22.5	18	152/149	L	17	9	3550	3250	930	1085	300
315/80R22.5	20	157/154	K	17.5	9	4125	3750	900	1076	312
295/80R22.5	18	152/149	M	18	9	3550	3250	900	1050	298



CARAWAY™

CW770

- Outstanding self-cleaning capability, powerful tractive and bearing capability
- Much longer service life due to sound puncture-resistant capability



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
11.00R20	18	152/149	F	19	8	3550	3250	930	1096	293
12.00R20	20	156/153	F	20	8.5	4000	3650	900	1136	315
12.00R20	18	154/151	F	20	8.5	3750	3450	830	1136	315



CARAWAY™

CW106

- Suitable for good road surface application
- With excellent anti-side-skid character, low rolling resistance
- Low heat generating, excellent high-speed driving character



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
11.00R20	18	152/149	J	16	8	3550	3250	930	1085	293
12R22.5	18	152/149	M	16	9	3550	3250	930	1085	300
295/80R22.5	18	152/149	M	17	9	3550	3250	900	1044	298
315/80R22.5	20	157/154	L	19	9	4125	3750	900	1076	312
275/80R22.5	16	147/144	M	14	8.25	3075	2800	830	1012	276



CARAWAY™

CW666

- The position of trailer wheel for long-distance transportation
- Suitable for on-road driving
- Soundly resistant to side-skidding; low rolling resistance; little noise; excellent high-speed performance
- Much higher mileage due to the low heat-generating and wear-resistant formula



● Recommend

● Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
385/65R22.5	24	164	K	15	11.75	5000	/	900	1072	389



CARAWAY™

CW758

- The position of trailer wheel for long-distance transportation
- Suitable for on-road driving
- Soundly resistant to side-skidding; low rolling resistance; little noise; excellent high-speed performance
- Much higher mileage due to the low heat-generating and wear-resistant formula



● Recommend

● Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
385/65R22.5	20	160	K	16	11.75	4500	/	900	1072	389



CARAWAY™

CW210

- EXceptional road holding and passing capability
- Good self-cleaning capacity, strongly wearing resistance to wear and puncture



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
10.00R20	18	149/146	F	20.5	7.5	3250	3000	930	1065	278
11.00R20	18	152/149	F	21	8	3550	3250	930	1096	293
12.00R20	20	156/153	F	21.5	8.5	4000	3650	900	1136	315



CARAWAY™

CW230

- Exceptional tractive and bearing capacity
- Exceptional self-cleaning, wear resistant, and puncture-resistant capability



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
11.00R20	18	152/149	F	24	8	3550	3250	930	1096	293
12.00R20	20	156/153	F	24.5	8.5	4000	3650	900	1136	315
12.00R20	18	154/151	F	24.5	8.5	3750	3450	830	1136	315



CARAWAY™

CW990

- Sound handling performance and powerful driving due to design of intersecting grooves and block patterns
- Even stress distribution can prevent lateral wear
- Much higher mileage due to low heat-generation and soundly wear-resistant formula



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
315/80R22.5	20	157/154	L	21	9	4125	3750	900	1082	312
12R22.5	18	152/149	M	21	9	3550	3250	930	1096	300



CARAWAY™

CW881

- Extraordinary bearing capacity and outstanding tractive
- Braking and skidding-resistant performance due to mixed pattern design



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
10.00R20	18	149/146	J	19	7.5	3250	3000	930	1054	278



CARAWAY™

CW882

- Excellent tractive and braking capability due to large pattern block and transverse pattern groove
- Low heat-generating, tearing-resistant, and wear-resistant design of tread
- Improved skidding-resistant capability and decreased irregular wear of tread due to the design of thin grooves



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
295/80R22.5	18	152/149	M	18	9	3550	3250	900	1050	298



CARAWAY™

CW191

- Outstanding handling and side-skidding-resistant performance
- Specially-designed grooves bottom can effectively prevent from being stuck in the bottom; exceptional self-cleaning capability
- Sound wear-resistant performance; low heat-generation in the shoulder; adaptive to high-speed and long-distance travelling
- Low-rolling resistance formula design can effectively decrease fuel consumption



- Recommend
- Forbidden

SIZE	PLY Rating	Load Index	Speed Symbol	Tread Depth (mm)	Standard Rim	Max Load Single(kg)	Max Load Dual(kg)	Pressure (Kpa)	Overall Diameter (mm)	Section Width (mm)
295/80R22.5	18	152/149	M	17	9	3550	3250	900	1044	298
12R22.5	18	152/149	M	17	9	3550	3250	930	1085	300

CARAWAY™

GRAND INTERNATIONAL GROUP



Caraway
Tire