



COMPASAL



BEYOND EXPECTATION

www.miamitireinternational.com

TO PROVIDE MORE HIGH-QUALITY PRODUCTS AND SERVICES FOR THE VEHICLE USERS AROUND THE WORLD



CPT76

[Product Features]

TRAILER

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)	EU-LABEL	
215/75R17.5	16PR	127/124	M	6	12	233	797	C	D 73
215/75R17.5	18PR	135/133	J	6	12	233	797	C	D 73
225/70R19.5	14PR	128/126	M	6.75	12.5	226	811	C	D 73
235/75R17.5	16PR	132/130	M	6.75	12.5	211	767	C	D 73
235/75R17.5	18PR	143/141	J	6.75	12.5	211	767	C	D 73
245/70R19.5	16PR	143/141	J	7.5	12.5	248	839	C	D 73
245/70R19.5	18PR	141/140	J	7.5	12.5	248	839	C	D 73
265/70R19.5	16PR	140/138	M	7.5	12.5	262	867	C	D 73
265/70R19.5	18PR	143/141	J	7.5	12.5	262	867	C	D 73
285/70R19.5	16PR	146/144	M	8.25	13.5	283	895	C	D 73
285/70R19.5	18PR	150/148	J	8.25	16	283	895	C	D 73
275/70R22.5	16PR	148/145	H	8.25	14.5	276	958	C	D 73
275/70R22.5	18PR	152/148	J	8.25	14.5	276	958	C	D 73
385/55R22.5	20PR	160	L	12.25	15.5	386	996	C	D 73
385/65R22.5	20PR	160	L	11.75	15.5	389	1072	C	D 73



CPD85

[Product Features]

DRIVE

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
315/80R22.5	20PR	156/150	K	9	20	312	1076



CPT75

[Product Features]

TRAILER

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
385/65R22.5	20PR	160	L	11.75	15.5	389	1072



CPD81

[Product Features]

DRIVE

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)	EU-LABEL		
10.00R20	18PR	149/146	K	7.5	20	254	1019	D	D	75
11R22.5	16PR	148/145	M	8.25	20	279	1054	D	D	75
215/75R17.5	16PR	127/124	M	6	15	233	797	D	D	75
215/75R17.5	18PR	135/133	M	6	15	233	797	D	D	75
225/70R19.5	14PR	128/126	M	6.75	15.5	226	811	D	D	75
235/75R17.5	16PR	132/130	M	6.75	15.5	211	767	D	D	75
235/75R17.5	18PR	143/141	J	6.75	15.5	211	767	D	D	75
245/70R19.5	16PR	136/134	K	7.5	15.5	248	839	D	D	75
245/70R19.5	18PR	143/141	J	7.5	12.5	248	839	D	D	75
265/70R19.5	16PR	140/138	M	7.5	15.5	262	867	D	D	75
265/70R19.5	18PR	143/141	M	7.5	12.5	262	867	D	D	75
275/70R22.5	16PR	148/145	H	8.25	18	276	958	D	D	75
275/70R22.5	18PR	152/148	J	8.25	18	276	958	D	D	75
285/70R19.5	16PR	146/144	M	8.25	16	283	895	D	D	75
285/70R19.5	18PR	150/148	J	8.25	16	283	895	D	D	75
295/80R22.5	18PR	152/149	M	9	20	298	1044	D	D	75
295/80R22.5	18PR	152/149	L	9	20	302	1044	D	D	75
315/70R22.5	20PR	154/150	M	9	20	312	1014	D	D	75
315/80R22.5	20PR	156/150	M	9	20	312	1076	D	D	75

THE WIDE SECTION





CPS60

[Product Features]

ALL POSITION

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)	EU-LABEL
7.50R16	14PR	122/118	L	6.5	13	215	803	C D 73
8.25R16	16PR	128/124	K	6.50H	14.5	235	855	C D 73
9.00R20	16PR	144/142	K	7	15.5	259	1019	C D 73
10.00R20	18PR	149/146	K	7.5	16.5	278	1054	C D 73
11.00R20	18PR	152/149	K	8	16	293	1085	C D 73
12.00R20	20PR	156/153	K	8.5	16	315	1125	C D 73
12.00R24	20PR	160/157	K	8.5	15	315	1226	C D 73
11R22.5	16PR	148/145	M	8.25	14.5	279	1054	C D 73
12R22.5	18PR	152/149	M	9	14.5	300	1085	C D 73
13R22.5	20PR	156/150	L	9.75	15.3	320	1124	C D 73
13R22.5	18PR	154/151	L	9.75	14.5	320	1124	C D 73
295/80R22.5	18PR	152/149	L	9	15.5	298	1044	C D 73
315/80R22.5	20PR	156/150	M	9	14.5	312	1076	C D 73

* NO M+S



CPD82

[Product Features]

DRIVE

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)	EU-LABEL
11R22.5	16PR	148/145	M	8.25	20	279	1054	D D 73
11R24.5	16PR	149/146	K	8.25	20	279	1104	D D 73
13R22.5	20PR	156/150	K	9.75	20	320	1124	D D 73
295/80R22.5	18PR	152/149	L	9	20	298	1044	D D 73
315/70R22.5	20PR	154/150	L	9	20	312	1014	D D 73
315/80R22.5	20PR	156/150	K	9	20	312	1076	D D 73



CPD26

[Product Features]

ALL POSITION

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
12R22.5	18PR	152/149	K	9	18	300	1084
315/80R22.5	20PR	156/150	K	9	20	312	1076

* NO M+S



CPS21

[Product Features]

ALL-POSITION

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)	EU-LABEL
11R22.5	14PR	144/142	M	8.25	14.5	279	1054	C D 73
11R22.5	16PR	148/145	M	8.25	14.5	279	1054	C D 73
11R24.5	14PR	146/143	M	8.25	14.5	279	1104	C D 73
11R24.5	16PR	149/146	M	8.25	14.5	279	1104	C D 73
12R22.5	18PR	152/149	M	9	14.5	300	1085	C D 73
20S/75R17.5	14PR	124/122	M	6	12	205	753	C D 73
21S/75R17.5	16PR	127/124	M	6	12	233	797	C D 73
21S/75R17.5	18PR	135/133	J	6	12	233	797	C D 73
22S/70R19.5	14PR	128/126	M	6.75	12.5	226	811	C D 73
23S/75R17.5	16PR	132/130	M	6.75	12.5	211	767	C D 73
23S/75R17.5	18PR	143/141	J	6.75	12.5	211	767	C D 73
24S/70R19.5	16PR	136/134	M	7.5	12.5	248	839	C D 73
24S/70R19.5	18PR	143/141	J	7.5	12.5	248	840	C D 73
26S/70R19.5	16PR	140/138	M	7.5	12.5	262	867	C D 73
26S/70R19.5	18PR	143/141	J	7.5	12.5	262	867	C D 73
27S/70R22.5	16PR	148/145	H	8.25	14.5	276	958	C D 73
27S/70R22.6	18PR	152/148	J	8.25	14.5	276	958	C D 73
28S/75R24.5	16PR	147/144	M	8.25	14.5	283	895	C D 73
28S/75R24.5	18PR	150/148	J	8.25	14.5	283	895	C D 73
29S/75R22.5	16PR	146/143	M	9	14.5	298	1014	C D 73
29S/80R22.5	18PR	152/149	M	9	15.5	298	1044	C D 73
29S/80R22.5	18PR	152/149	M	9	15.5	302	1044	C D 73
31S/70R22.5	20PR	154/150	M	9	15.5	312	1014	C D 73
31S/80R22.5	20PR	156/150	M	9	15.5	312	1076	C D 73
38S/55R22.5	20PR	160	L	12.25	15.5	386	996	C D 73
38S/65R22.5	20PR	160	L	11.75	15.5	389	1072	C D 73

* THE WIDE SECTION

* NO M+S



CPS25

[Product Features]

STEER AND TRAILER

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
11R22.5	14PR	144/142	M	8.25	13	279	1054
11R22.5	16PR	146/143	M	8.25	13	279	1054
11R24.5	14PR	146/143	M	8.25	11	279	1104
11R24.5	16PR	149/146	M	8.25	11	279	1104
12R22.5	18PR	152/149	M	9	14.5	300	1085
28S/75R24.5	14PR	144/141	M	8.25	11	283	1050
28S/75R24.5	16PR	147/144	M	8.25	11	283	1050
29S/75R22.5	14PR	144/141	M	9	11	298	1014
29S/75R22.5	16PR	146/143	M	9	11	298	1014
29S/80R22.5	18PR	152/149	M	9	14.5	298	1044
31S/80R22.5	20PR	156/150	M	9	14.5	312	1076

* NO M+S



CPS68

[Product Features]

STEER AND TRAILER M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
11.00R20	18PR	152/149	K	8	17	293	1085



CPS91

[Product Features]

STEER AND TRAILER M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
12.00R24	20PR	160/157	K	8.5	16	315	1226



CPS92

[Product Features]

STEER AND TRAILER M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
12.00R24	20PR	160/157	K	8.5	16	315	1226



CPD68

[Product Features]

DRIVE M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
8.25R16LT	16PR	128/124	K	6.50H	14.5	235	855
9.00R20	16PR	144/142	J	7	15.5	255	1030
10.00R20	18PR	149/146	J	7.5	16.5/20	278	1065

* NO M+S



CPD68+

[Product Features]

DRIVE

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
11.00R20	18PR	152/149	K	8	18.5	293	1085
12.00R20	20PR	156/153	K	8.5	19.5	315	1125



CPD86

[Product Features]

DRIVE

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
11.00R20	18PR	152/149	G	8	20	293	1096
12.00R20	20PR	156/153	G	8.5	20	315	1136
11R22.5	16PR	146/143	K	8.25	20	279	1065
12R22.5	18PR	152/149	G	9	22	300	1096
13R22.5	20PR	156/150	G	9.75	22	320	1136

* NO M+S



CPD27

[Product Features]

ALL POSITION

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
12R22.5	18PR	152/149	K	9	18	300	1084
205/75R17.5	14PR	124/122	M	6	15	205	753
215/75R17.5	14PR	135/133	J	6	15	233	797
215/75R17.5	18PR	135/133	J	6	15	233	797
225/70R19.5	14PR	128/126	M	6.75	15.5	226	811
235/75R17.5	14PR	143/141	J	6.75	16	211	767
235/75R17.5	18PR	143/141	J	6.75	16	211	767
245/70R19.5	16PR	136/134	M	7.5	14.5	248	839
245/70R19.5	18PR	141/140	J	7.5	14.5	248	839
265/70R19.5	16PR	140/138	M	7.5	15.5	262	867
265/70R19.5	18PR	143/141	J	7.5	15.5	262	867
285/70R19.5	16PR	146/144	M	8.25	16.5	283	895
285/70R19.5	18PR	150/148	J	8.25	16.5	283	895
315/70R22.5	20PR	154/150	L	9	20	312	1014
315/80R22.5	20PR	156/150	K	9	18	300	1084

* NO M+S



CPD83

Product Features]

DRIVE

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
10.00R20	18PR	149/146	K	7.5	18	254	1019



CPS61

Product Features]

STEER AND TRAILER

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
6.50R16	12PR	110/105	L	5.50F	11	185	750



CPS62

Product Features]

STEER AND TRAILER

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
7.00R16	14PR	118/114	L	5.50F	11	200	775

* NO M+S



CPD88

Product Features]

DRIVE

M+S

SIZE	PLY	LOAD INDEX	SPEED LEVEL	STANDARD RIM	TREAD DEPTH	SECTION WIDTH(MM)	OUTER DIAMETER(MM)
11R22.5	14PR	144/142	K	8.25	20	279	1054
11R22.5	16PR	148/145	M	8.25	20	279	1054
11R24.5	14PR	146/143	K	8.25	20	279	1104
11R24.5	16PR	149/146	K	8.25	20	279	1104
285/75R24.5	14PR	144/141	L	8.25	20	283	1050
285/75R24.5	16PR	147/144	L	8.25	20	283	1050
295/75R22.5	14PR	144/142	K	9	20	298	1014
295/75R22.5	16PR	146/143	K	9	20	298	1014