



RAPID

PCR CATALOGUE





P309



Silent Grooves on Main Ribs

Same groove void ratio at any tire cross section for smooth air flow to effectively reduce pattern noise. It connects the central grooves as silencer.



Silent Pitch Arrangement

Silent driving experience is achieved by optimized pitch width hand arrangement, pitch displacement design to reduce tire harmonic noise.



Tilted Sipes on Center Rib

Center rib ensures straight line stability and improves acceleration.



Special Shoulder Block Design

The special design with sipes at the shoulder block effectively reduces the shoulder heat generation and resonance during tire rolling.

U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A

Sizes	LI&SS	Approval Rim	Max Load	
			Kg	LBS
155/65R13	73 T	4½~5½J	3365	365
155/70R13	75 T	4~5J	387	387
155/80R13	79 T	4~5J	437	437
165/65R13	77 T	4½~6J	412	412
165/70R13	79 T	4~5½J	437	437
175/60R13	77 T	5½~6J	412	412
175/65R13	80 T	5~6J	450	450
175/70R13	82 T	4½~6J	475	475
185/70R13	86 H/I	4½~6J	530	530
155/65R14	75 T	4½~5½J	387	387
165/60R14	75 H	4½~6J	387	387
165/70R14	81 T	4~5½J	462	462
165/70R14	85 T	4~5½J	515	515
175/65R14	82 H/T	5~6J	475	475
175/65R15	84 H	5~6J	500	500
175/70R14	84 H/T	4½~6J	500	500
175/70R14	88 H	4½~6J	560	560
185/60R14	82 H	5~6½J	475	475
185/65R14	86 H/T	5~6½J	530	530
185/70R14	88 H/T	4½~6J	560	560
195/60R14	86 H	5½~7J	530	530
195/70R14	91 H/I	5~6½J	615	615
205/70R14	95 T	5~7J	690	690
205/70R14	98 T	5~7J	750	750
185/55R15	82 H/V	5~6½J	475	475
185/60R15	84 H	5~6½J	500	500

Sizes	LI&SS	Approval Rim	Max Load	
			Kg	LBS
185/60R15	88 H	5~6½J	560	560
185/65R15	88 H	5~6½J	560	560
195/60R15	88 H/V	5½~7J	560	560
195/65R15	91 H/V	5½~7J	615	615
195/65R15	95 H	5½~7J	690	690
205/60R15	91 H/V	5½~7½J	615	615
205/60R15	95 H	5½~7½J	690	690
205/60R15	95 V	5½~7½J	690	690
205/65R15	94 H/V	5½~7½J	670	670
205/70R15	96 H	5~7J	710	710
215/65R15	96 H	6~7½J	710	710
215/70R15	98 H	5½~7J	750	750
185/50R16	85 V	5½~6½J	515	515
185/55R16	87 V	5½~6½J	545	545
195/60R16	89 H	5½~7J	580	580
205/55R16	91 V	5½~7½J	615	615
205/55R16	91 W	5½~7½J	615	615
205/55ZR16	94 WXL	5½~7½J	670	670
205/60R16	92 H/V	5½~7½J	630	630
205/65R16	99 H	5½~7½J	775	775
215/60R16	95 V	6~7½J	690	690
215/60R16	99 HXL	6~7½J	775	775
215/60R16	99 VXL	6~7½J	775	775
225/50ZR16	96 W	6~8J	710	710
225/60R16	98 H	6~8J	750	750



UHP Tyre
P609



U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A



Asymmetric Paltern

To increase the contact area of the outside part of the tire with its cornering sharpness.It ensures good traction and let the driver feel confident at high speed cornering.At the same time,it improves the wear aspect and evenness.



Tilted Sipes on Center Rib

Center rib ensures straight line stability and improves acceleration.



Green Tread Compound With More Silica

Silica reduces the friction between the rubber moleculars to decrease energy loss and hence reduce rolling resistance.



Special Outsider Shoulder Block Design

When cornering at high speed,tread shoulder block deforms easily under the transversal force.The wide and big design of the shoulder block and stabilizing rib reduces the deformation at cornering,hence it ensures high speed stability and brings precise driving experience.

Sizes	LI&SS	Approval Rim	Max Load Kg	Max Load LBS
220S/60R14	88 T	5½-7½J	560	1235
195/50R15	82 V	5½-7J	475	1047
195/55R15	83 H/V	5½-7J	515	1135
195/45R16	84 V	6-7½J	500	1102
195/50R16	84 V	5½-7J	500	1102
195/50R16	88 V	5½-7J	560	1235
195/55R16	87 V	5½-7J	545	1201
195/55RF16	87 V	5.5-7J	545	1201
205/45ZR16	87 W	6½-7½J	545	1201
205/50ZR16	87 W	5½-7½J	545	1201
205/55R16	81 H/V	5½-7½J	615	1356
205/55ZR16	91 W	5½-7½J	615	1356
205/55ZRF16	91 W	5½-7½J	615	1356
215/45R16	86 V	7½J	530	1168
215/55ZR16	97 W	6-7½J	730	1609
225/55R16	95 V	6-8J	690	1521
225/55R16	99 HXL	6-8J	775	1709
225/55R16	99 VXL	6-8J	775	1709
205/40R17	80 V	7-8J	500	1102
205/40ZR17	84 WXL	7-8J	500	1102
205/45ZR17	84 W	6½-7½J	560	1235
205/45ZR17	88 WXL	6½-7½J	560	1235
205/45ZR17	88 W	6.5-7.5J	560	1235
205/50ZR17	93 WXL	5½-7½J	650	1433
205/50ZRF17	93 W	5½-7½J	650	1433
205/55ZR17	95 XL	6-7J	690	1521
215/40ZR17	87 WXL	7½-9J	545	1201
215/45R17	91 W	7-8J	615	1356
215/50ZR17	95 W	6-7½J	690	1521
215/55ZR17	98 WXL	6-7½J	750	1653
225/45ZR17	94 WXL	7-8½J	670	1477
225/45ZRF17	94 W	7-8½J	670	1477
225/50ZR17	98 W	6-8J	750	1653
225/55ZR17	101 W	6-8J	825	1819
235/45ZR17	97 WXL	7½-9J	730	1609
235/50ZR17	96 W	7-8J	710	1565
235/50R17	100 V	7-8J	800	1764
235/50ZR17	100 W	7-8J	800	1764
235/55ZR17	103 WXL	6½-8½J	875	1929
245/40ZR17	95 W	8-9½J	690	1521
245/45ZR17	99 WXL	7½-9J	775	1709
215/35ZR18	84 WXL	7½-8½J	500	1102
215/40ZR18	89 WXL	7-8J	580	1279
215/55R18	99 V	6½-7½J	775	1709
225/40ZR18	92 WXL	7½-9J	630	1389

Sizes	LI&SS	Approval Rim	Max Load Kg	Max Load LBS
225/40ZRF18	92 W	7.5-9J	630	1389
225/45ZR18	95 WXL	7-8½J	690	1521
235/40ZR18	95 WXL	8-9½J	690	1521
235/45ZR18	98 YXL	7½-9J	750	1653
235/50R18	101 V	7-8J	825	1819
235/50ZR18	101 W	7-8J	825	1819
245/40ZR18	97 WXL	8-9½J	730	1609
245/40ZRF18	97 W	8-9.5J	730	1609
245/45ZR18	100 WXL	7½-9J	800	1764
245/45ZR18	96 W	7½-9J	710	1565
245/45ZRF18	100 W	7.5-9J	800	1764
245/50ZR18	100 W	7-8J	800	1764
255/35ZR18	94 W	8½-10J	670	1477
255/45ZR18	103 WXL	8-9½J	875	1929
265/35ZR18	97 W	9-10J	730	1609
215/35ZR19	85 WXL	7-8J	515	1135
225/35ZR19	88 W	7½-9J	560	1245
225/55R19	99 V	6½-7½J	775	1709
235/35ZR19	91 W	8-9½J	615	1356
245/35ZR19	93 W	8-9½J	650	1433
245/55R19	103 V	7-8J	875	1929
255/30ZR19	91 Y	8½-9½J	615	1356
255/35ZR19	96 Y	8½-10J	710	1565
255/40R19	100 V	8½-9½J	800	1764
265/30ZR19	93 W	9-10J	650	1433
275/30ZR19	96 WXL	9-10J	710	1565
285/45ZR19	111 WXL	9-10J	1090	2403
225/35ZR20	90 W	7½-9J	600	1323
245/35ZR20	95 W	8-9½J	690	1521
245/45ZR20	99 W	7½-8½J	775	1709
245/50ZR20	102 W	7-8J	850	1874
255/35ZR20	97 W	8½-9½J	730	1609
255/45ZR20	105 W	8-9J	925	2039
265/45ZR20	104 W	8½-9½J	900	1984
275/40ZR20	106 Y	9-11J	950	2094
275/45R20	110 V	8½-10½J	1060	2337
275/55ZR20	117 WXL	7½-9½J	1285	2833
285/50R20	116 V	8-10J	1250	2756
315/35ZR20	110 Y	10½-11½J	1060	2337
295/35ZR21	107 Y	10-11J	975	2149
265/35ZR22	102 W	9-10½J	850	1874
285/35ZR22	112 W	9½-11J	1120	2469
305/40ZR22	114 W	10-12J	1180	2601
305/45ZR22	118 W	9½-11½J	1320	2910
305/35ZR24	112 W	10-12J	1120	2469



SUV Tyre
ECOSAVER



U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A



Special Shoulder Design

Tyre shoulder strip resist the uneven wear



Quite-ride Pitch Alignment

Optimized tread pitch width and alignment quiet resonance and the road noise it creates



Wide Grooves Design

Wide grooves on the shoulder fully radiate the heat



Central Rib

High speed stability with handling response



Special Bead Design

Special bead design guarantee long tyre life

Sizes	LI&SS	Approval Rim	Max Load Kg	Max Load LBS
215/70R15	98 H/T	5½~7J	750	1653
215/75R15	100 H	5½~7J	800	1764
225/70R15	100 H	6~7½J	800	1764
225/75R15	102 H	6~7½J	850	1874
235/75R15	105 H	6~8J	925	2039
265/70R15	110 H	7~9J	1060	2337
265/70R15	112 H	7~9J	1120	2469
205/60R16	96 V	5½~6½J	710	1565
215/60R16	95 H	6~7½J	690	1521
215/60R16	99 H	6~7½J	775	1709
215/65R16	98 H	6~7½J	750	1653
215/70R16	100 H	5½~7J	800	1764
225/60R16	98 H	6~8J	750	1653
225/65R16	100 H	6~8J	800	1764
225/70R16	102 T	6~7½J	850	1874
235/60R16	100 H	6½~8½J	800	1764
235/65R16	103 T	6½~8½J	875	1929
235/70R16	106 H/T	6~8J	950	2094
245/70R16	107 H	6½~8J	975	2149
245/70R16	111 H	6½~8J	1090	2403
245/75R16	111 H	6½~8J	1090	2403
255/65R16	109 H	7~9J	1030	2271
255/70R16	111 T	6½~8½J	1090	2403
265/70R16	112 H/T	7~9J	1120	2469
265/75R16	116 H	7~9J	1250	2756
275/70R16	114 H	7~9J	1180	2601
215/60R17	96 H	6~7½J	710	1565
225/60R17	99 H	6~8J	775	1709
225/65R17	102 H	6~8J	850	1874
225/70R17	108 T	6~7½J	1000	2205

Sizes	LI&SS	Approval Rim	Max Load Kg	Max Load LBS
235/60R17	102 H	6½~7½J	850	1874
235/60R17	106 V	6½~7½J	950	2094
235/65R17	104 H	6½~8½J	900	1984
235/65R17	108 H	6½~8½J	1000	2205
235/70R17	107 H	6~8J	975	2149
235/70R17	111 H	6~8J	1090	2403
245/65R17	107 H	7~8½J	975	2149
245/70R17	108 T	6½~8J	1000	2205
255/65R17	110 H	7~9J	1060	2337
255/70R17	110 T	6½~8½J	1060	2337
255/70R17	112 T	6½~8½J	1120	2469
265/65R17	112 H/T	7½~9½J	1120	2469
265/70R17	113 H	7~9J	1150	2535
275/60R17	110 H	7½~9½J	1060	2337
275/65R17	115 H	7½~9½J	1215	2679
275/65R17	119 H	7½~9½J	1360	2998
285/65R17	116 H/T	8~10J	1250	2756
225/60R18	100 H	6~8J	800	1764
235/60R18	103 H	6½~8½J	875	1929
245/60R18	104 H	7~8½J	900	1984
255/70R18	112 H	6½~8½J	1120	2469
265/60R18	110 H	7½~9½J	1060	2337
285/60R18	120 H	8~10J	1400	3086
255/55R18	109 V	7½~8½J	1030	2271
235/55R18	100 V	7~8J	800	1764
235/65R18	106 V	6½~7½J	950	2094
235/65R18	110 V	6½~7½J	1060	2337
255/50R19	103 V	7½~8½J	875	1929
255/50ZR19	107 Y	7½~8½J	975	2149





ECOLANDER



3-D Walls Design

Two longitudinal grooves with 3-D grooves walls evacuate water and resist aquaplaning



Linked Blocks Design

Linked blocks good adhesion in dry conditions and excellent stability, high-speed controllability



Full Touch Design

Large contact patch make sure you get all the grip stability, high-speed controllability



Special Grooves Design

Sipes in groove make sure good adhesion, particularly in the wet and snow



Reinforced Compound Inside

Reinforced compound and side wall make sure to meet all roads situation

U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A

Sizes	LI&SS	Approval Rim	Max Load kg	Max Load LBS
215/70R16	99 T	5½~7J	775	1709
225/70R16	101 T	6~7½J	825	1819
225/70R16	107 T	6~7½J	975	2149
235/70R16	104 T	6~8J	900	1984
235/70R16	106 T	6~8J	950	2094
245/70R16	106 T	6½~8J	950	2094
245/70R16	111 T	6½~8J	1090	2403
255/70R16	111 T	6½~8½J	1030	2271
255/70R16	109 T	6½~8½J	1030	2271
265/70R16	112 T	7~9J	1120	2469
265/70R16	111 T	7~9J	1090	2403
265/65R17	110 T	7½~9½J	1060	2337
265/65R17	112 T	7½~9½J	1120	2469
265/70R17	113 T	7~9J	1150	2535
275/65R17	115 T	7½~9½J	1215	2679
31*10.50R15LT	109 S	7~9J	1030	2270

Sizes	LI&SS	Approval Rim	Max Load kg	Max Load LBS
LT215/75R15	106/103 S	5½~7J	950/875	2095/1930
LT225/75R15	108/104 S	6~7J	1000/900	2205/1985
LT235/75R15	110/107 S	6~7J	1060/975	2335/2150
LT215/85R16	115/112 S	5½~7J	1215/1120	2680/2470
LT225/75R16	115/112 S	6~7J	1215/1120	2680/2470
LT235/85R16	120/116 S	6~7½J	1380/1260	3042/2778
LT245/75R16	120/116 S	6½~8J	1380/1260	3042/2778
LT265/70R16	121/118 R	7~8½J	1450/1320	3195/2910
LT265/75R16	123/120 S	7~8J	1550/1400	3415/3085
LT285/75R16	126/123 R	7½~9J	1700/1550	3750/3415
LT245/75R17	121/118 S	6½~7½J	1450/1320	3195/2910
LT265/70R17	121/118 S	7~8½J	1450/1320	3195/2910
LT285/70R17	121/118 S	7½~9J	1450/1320	3195/2910
LT315/70R17	121/118 R	8~11J	1450/1320	3195/2910
305/70R17LT	121/118 R	8~9½J	1450/1320	3195/2910
LT275/65R18	123/120 S	7½~9J	1550/1400	3415/3085



C Tyre
EFFIVAN



Three wide vertical grooves in tread lead to fast water evacuation and shorter braking distance, which increase the driving safety greatly.



Tiny pattern groove on tyre crown lower the rolling noise effectively, meanwhile, the rigidity of tread is more well-distributed which reduce abnormal wearing and increase mileage.



Scientific pattern design and low rolling noise brings in more comfortable driving experience.



U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A

Sizes	LI&SS	Approval Rim	Max Load kg	Max Load LBS
155R13C	85/83 S	4~5J	515/487	1135/1074
165R13C	94/93 R	4-5J	670/650	1475/1435
165/70R13C	88/86 T	4-5J	560/530	1235/1170
175R13C	97/95 R	4½-5½J/4.50B 5.00B	730/690	1610/1520
175R13C	97/95 S	4½-5½J/4.50B 5.00B	730/690	1610/1520
175R14C	99/98 R	4½~5½J	775/750	1710/1655
175/70R14C	95/93 S	4½~5½J	690/650	1520/1435
165R14C	96/95 R	4~5J	710/690	1565/1520
185R14C	102/100Q	5~6J	850/800	1875/1765
195R14C	106/104Q	5~6J	950/900	2095/1985
205R14C	109/107S	5½~6½J	1030/975	2270/2150
185R15C	103/102R	5~6J	875/850	1930/1875
195R15C	106/104Q	5~6J	950/900	2095/1985
195/70R15C	104/102R	5~6J	900/850	1985/1875
205/70R15C	106/104 R	5½~6½J	950/900	2095/1985
215/65R15C	104/102 T	6~7J	900/850	1985/1875

Sizes	LI&SS	Approval Rim	Max Load kg	Max Load LBS
215/70R15C	104/101 S	5½~7J	900/825	1985/1820
215/70R15C	109/107 S	5½~7J	1030/975	2270/2150
225/70R15C	112/110 S	6~7J	1120/1060	2470/2335
185/75R16C	104/102 R	5~6J	900/850	1985/1875
195/65R16C	104/102 R	5½~6J	900/850	1985/1875
195/65R16C	104/102 T	5½~6J	900/850	1985/1875
195/75R16C	107/105 R	5~6J	975/925	2150/2040
205/65R16C	107/105 R	5½~6½J	975/925	2150/2040
205/65R16C	107/105 T	5½~6½J	975/925	2150/2040
205/75R16C	110/108 R	5½~6½J	1060/2335	1000/2205
215/65R16C	109/107 R	6~7J	1030/975	2270/2150
215/65R16C	109/107 T	6~7J	1030/975	2270/2150
215/75R16C	116/114 R	5½~7J	1250/1180	2755/2601
215/75R16C	113/111 R	5½~7J	1150/1090	2535/2405
225/65R16C	112/110 R	6~7J	1120/1060	2470/2335
235/65R16C	115/113 R	6½~7½J	1215/1150	2680/2535



SNOW Tyre ECOSNOW



U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A



Traction Pattern Design

Open lateral slit and sip enhance the water drainage and snow traction



Big Block Design

Rib and large size block enhance the handling



3-D sipes

Stable the handling in both wet and dry
Better irregular wear resistance



Silica Compound Design

Unique silica tread compound enhance the snow and wet handling

Sizes	LI&SS	Approval Rim	Max Load	
			Kg	LBS
175/65R14	82 H	5~6J	475	1047
185/60R14	82 H	5~6½J	475	1047
185/65R14	86 H	5~6½J	530	1168
185/65R15	88 H	5~6½J	560	1235
195/55R15	85 H	5½~7J	515	1135
195/60R15	88 H	5½~7J	560	1235
195/65R15	91 H	5½~7J	615	1356
205/65R15	94 H	5½~7½J	670	1477
205/55R16	91 H/V	5½~7½J	615	1356
205/60R16	96 HXL	5½~7½J	710	1565
215/55R16	97 H/V	6~7½J	730	1609
215/55R16	97 V	6~7½J	730	1609
215/55R16	97 H	6~7½J	730	1609
215/60R16	99 H	6~7½J	775	1709
215/65R16	98 H	6~7½J	750	1653
225/55R16	99 V	6~8J	775	1709
225/45R17	94 V	7~8½J	670	1477
225/40R18	92 V	7½~9J	630	1389
245/45R18	100 V	7½~9J	800	1764
255/55R18	109 V	7~9J	1030	2271





FREEZE S1



Full Touch Design

Asymmetric design offer stonger lateral and longitudinal braking on snow and water



Traction Pattern Design

Multiple open lateral slit and sip enhance the water drainage and snow traction



V-Sharp Design

The V-sharp design guarantee the drainage and handling stability



Multi-wave Sipes Design

Multi-wave sipes to increase the tread block rigidity,higher sipe density to emphasize the ice traction

Sizes	LI&SS	Approval Rim	Max Load	
			Kg	LBS
165/70R13	83 T	4~5½J	437	963
175/70R14	88 T	4½~6J	560	1235
185/60R15	88 H	5~6½J	500	1102
195/55R16	91 H	5½~7J	545	1201
195/70R15C	104/101 S	5½~6½J	900/825	1985/1820
225/55ZR17	101 H	6~8J	825	1819
235/55ZR17	103 H	6½~8½J	875	1929

U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A





ECOSNOW4x4



V-Sharp Design

The V-sharp central spine guarantee the handling stability




Traction Pattern Design

Open lateral slit enhance the water drainage and snow traction



3-D Sipes

Stable the handling in both wet and dry
Better irregular wear resistance



Silica Compound Design

Unique silica tread compound enhance the snow and wet handling

Sizes	LI&SS	Approval Rim	Max Load	
			Kg	LBS
215/70R16	100 T	5½~7J	800	1764
235/60R16	100 H	6½~8½J	800	1764
235/70R16	106 T	6~8J	950	2094
245/70R16	107 T	6½~8J	975	2149
255/65R16	109 T	7~9J	1030	2271
265/70R16	112 T	7~9J	1120	2469
225/60R17	99 H	6~8J	775	1709
235/65R17	108 H	6½~8½J	1000	2205
225/65R17	102 Q	6~8J	850	1874

U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A





XTERRAIN



Wider ground contact design to improve the ground adhesion



Strong lateral block pattern of shoulder, provide excellent driving force and trafficability



Two closely reinforcement pattern design, can reduce the risk of the damage in poor road conditions



Compact protection convex block of sidewall can reduce the damage in driving to minimum.

U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A

Sizes	LI&SS	Approval Rim	Max Load	
			Kg	LBS
LT265/75R16	123/120 Q	7~8 J	1550/1400	3415/3085
LT265/75R16	119/116 Q	7~8 J	1360/1250	3000/2755
LT285/75R16	126/123 Q	7½~9 J	1700/1550	3750/3415
LT285/75R16	122/119 Q	7½~9 J	1500/1360	3305/3000
LT265/70R17	121/118 Q	7~8½ J	1450/1320	3195/2910
LT265/70R17	118/115 Q	7~8½ J	1320/1215	2910/2680
LT285/70R17	121/118 Q	7½~9 J	1450/1320	3195/2910
LT285/70R17	121/118 Q	7½~9 J	1450/1320	3195/2910
LT295/70R17	121/118 Q	7½~10 J	1450/1320	3195/2910
33×12.50R17LT	120 Q	8½~11 J	1400	3085
33×12.50R17LI	114 Q	8½~11 J	1180	2600
LT275/65R18	123/120 Q	7~9 J	1550/1400	3415/3085
33×12.50R18LT	118 Q	8½~11 J	1320	2910
LT285/55R20	122/119 Q	8~10 J	1500/1360	3305/3000
LT285/55R20	117/114 Q	8~10 J	1285/1180	2835/2600
33×12.50R20LT	114 Q	8½~11 J	1180	2600





BLUE SNOW




Special 'V' Style Directional Pattern

Excellent performance of draining away water and snow. The special design effects handling stability when it rained or snowed.



Full Perforation Pipes Pattern

Tread blocks perform more soft and more contact to the road surface due to the Full-Perforation-Pipes-Pattern. The powerful force between tread and road surface produces excellent handling and braking. It ensures the nice driving experience.



Circumferential Direction Stereoscopic Sips

Around the circumferential direction, arranges many stereoscopic sips. This design allows safe driving when going straight and in corners thanks to the added grip force especially on the ice road.

U.T.Q.G TREADWEAR:400 TRACTION:A TRMPEATURE:A

Sizes	LI&SS	Approval Rim	Max Load	
			Kg	LBS
175/65R14	82 H	5~6J	475	1047
185/60R14	82 H	5~6½J	475	1047
185/65R14	86 H	5~6½J	530	1168
185/65R15	88 H	5~6½J	560	1235
195/55R15	85 H	5½~7J	515	1135
195/60R15	88 H	5½~7J	560	1235
195/65R15	91 V	5½~7J	615	1356
195/65R15	95 V	5½~7J	690	1521
205/55R16	91 V	5½~7½J	615	1356
205/55R16	94 V	5½~7½J	670	1477
205/60R16	96 H	5½~7½J	710	1565
205/65R15	94 H	5½~7½J	670	1477
215/55R16	97 V	6~7½J	730	1609
215/60R16	99 H	6~7½J	775	1709
215/65R16	98 H	6~7½J	750	1653
225/40R18	92 H	7½~9J	630	1389
225/45R17	94 V	7~8½J	670	1477
225/55R16	99 V	6~8J	775	1709
245/45R18	100 V	7½~9J	800	1764
255/55R18	109 V	7~9J	1030	2271

