



SPORTRAK
— just run just win —

www.miamitireinternational.com



SPORTRAK TIRE

SPORTRAK
— just run just win —



 **SPORTTRAK**

— just run just win —

PCR TIRES

WWW.SPORTRAKTIRE.COM



SP716

ALL SEASON HP TIRE

Product features



Criss-cross grooves design

Criss-cross grooves design enhance water evacuation, effectively prevent tire lateral slip on wet road.



Centre wide ribs design

Central rib combined with horizontal grooves provides nice stability, excellent acceleration and brake performance at high speed.



Performance Test



SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O. D (MM)	S. W (MM)	Standard Rim	U.T.O.G				
155/65R13	73T	532	157	4½J	380 A A				
155/70R13	75T	548	157	4½J	380 A A				
155/80R13	79T	578	157	4½J	380 A A	E	C	70dB	C1
165/65R13	77T/77H	544	170	5J	380 A A				
165/70R13	79T/79H	562	170	5J	380 A A	E	C	70dB	C1
165/80R13	83T	594	165	4½J	380 A A	C	C	70dB	C1
175/60R13	77H	540	177	5J	380 A A	E	C	70dB	C1
175/70R13	82T/82H	576	177	5J	380 A A	E	C	70dB	C1
185/70R13	86T/86H	590	189	5½J	380 A A				
155/65R14	75T/75H	558	157	4½J	380 A A				
165/60R14	75T/75H	554	170	5J	380 A A				
165/65R14	79H	570	170	5J	380 A A	E	C	70dB	C1
165/70R14	81T	588	170	5J	380 A A				
175/65R14	82T/82H	584	177	5J	380 A A	E	C	70dB	C1
175/65R14	86T/86H XL	584	177	5J	380 A A				
175/70R14	84T/84H	602	177	5J	380 A A	E	C	70dB	C1
185/60R14	82H	578	189	5½J	380 A A	E	C	70dB	C1
185/65R14	86T/86H	596	189	5½J	380 A A	C	C	70dB	C1
185/70R14	88T/88H	616	189	5½J	380 A A	C	C	70dB	C1
195/60R14	86H	590	201	6J	380 A A	C	C	71dB	C1
195/65R14	89H	610	201	6J	380 A A	C	C	71dB	C1
195/70R14	91T/91H	630	201	6J	380 A A	C	C	71dB	C1
195/70R14	95H XL	630	201	6J	380 A A				
195/75R14	92T/92H	648	196	5½J	380 A A				
205/60R14	88H	602	209	6J	380 A A	E	C	71dB	C1
205/70R14	98T XL	644	209	6J	380 A A	B	C	72dB	C1
165/65R15	81T/81H	595	170	5J	380 A A				
175/55R15	77T/77H	573	182	5½J	380 A A				
175/60R15	81H	591	177	5J	380 A A	E	C	70dB	C1
175/65R15	84H	609	177	5J	380 A A	C	C	70dB	C1
185/55R15	82V	585	194	6J	380 A A	E	C	70dB	C1
185/60R15	84H	603	189	5½J	380 A A	C	C	70dB	C1
185/60R15	88H XL	603	189	5½J	380 A A	C	C	70dB	C1
185/65R15	88T/88H	621	189	5½J	380 A A	C	C	70dB	C1
195/50R15	82V	577	201	6J	380 A A	E	C	71dB	C1
195/55R15	85V	595	201	6J	380 A A	E	C	71dB	C1
195/60R15	88H/88V	615	201	6J	380 A A	C	C	71dB	C1
195/65R15	91H/91V	635	201	6J	380 A A	C	C	71dB	C1
195/70R15	97S XL	655	201	6J	380 A A				
205/50R15	86V	587	214	6½J	380 A A				
205/60R15	91H/91V	627	209	6J	380 A A				
205/65R15	94H/94V	647	209	6J	380 A A	C	C	71dB	C1
205/70R15	96H	669	209	6J	380 A A	C	C	71dB	C1
215/65R15	100H XL	661	221	6½J	380 A A	B	C	72dB	C1
215/65R15	96H	661	221	6½J	380 A A				
215/70R15	98T	683	221	6½J	380 A A	C	C	71dB	C1
225/60R15	96H	651	228	6½J	380 A A				
225/70R15	100T/100H	697	228	6½J	380 A A	C	C	71dB	C1
185/55R16	83H/83V	610	194	6J	380 A A				
195/50R16	84H/84V	602	201	6J	380 A A	E	C	71dB	C1
195/55R16	87H/87V	620	201	6J	380 A A	C	C	71dB	C1
205/50ZR16	87W	612	214	6½J	380 A A	C	C	71dB	C1
205/55R16	91V	632	214	6½J	380 A A				
205/55ZR16	91W	632	214	6½J	380 A A	C	C	71dB	C1
205/55ZR16	94W XL	632	214	6½J	380 A A				
205/60R16	92H/92V	652	209	6J	380 A A	C	C	71dB	C1
205/65R16	95V	672	209	6J	380 A A	C	C	71dB	C1
215/55ZR16	97W XL	642	226	7J	380 A A	B	C	72dB	C1
215/60R16	95H/95V	664	221	6½J	380 A A	C	C	71dB	C1
215/65R16	98H	686	221	6½J	380 A A	C	C	71dB	C1
215/70R16	100T/100H	708	221	6½J	380 A A				
225/50ZR16	92W	632	233	7J	380 A A	C	C	71dB	C1
225/50ZR16	96W XL	632	233	7J	380 A A	B	C	72dB	C1
225/55ZR16	99W XL	654	233	7J	380 A A	B	C	72dB	C1
225/60R16	98H	676	228	6½J	380 A A	C	C	71dB	C1
225/60R16	102H XL	676	228	6½J	380 A A	B	C	72dB	C1
225/70R16	103T/103H	722	228	6½J	380 A A				



SP726

UHP TIRE

Product features



Asymmetric tread design

four wide grooves design provide effective drainage and sufficient wet safety performance



Innovative technology

willow leaf-shaped biomimetic tread block design adopting willow-shaped biomimetic pattern block design inside, effectively prevent abnormal wear of pattern block corners, together with "s" shaped on tread grooves, bring soft, silence and comfort



Performance Test



SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O.D (MM)	S.W (MM)	Standard Rim	U.T.O.G	E	B	70dB	C1
195/50R15	82V	577	201	6J	320 A A	E	B	70dB	C1
195/55R15	85V	595	201	6J	320 A A	E	B	70dB	C1
235/60R15	98H/98V	663	240	7J	320 A A	---	---	---	---
245/60R15	101H/101V	675	248	7J	320 A A	---	---	---	---
195/45R16	84V XL	582	195	6½J	320 A A	E	B	71dB	C1
205/45ZR16	87W XL	590	206	7J	320 A A	E	B	71dB	C1
205/50ZR16	91W XL	612	214	6½J	320 A A	C	B	71dB	C1
205/55ZR16	91W	632	214	6½J	320 A A	E	B	70dB	C1
215/40ZR16	86W XL	578	218	7½J	320 A A	---	---	---	---
215/55ZR16	97W XL	642	226	7J	320 A A	C	B	71dB	C1
225/50ZR16	96W XL	632	233	7J	320 A A	E	B	71dB	C1
225/55ZR16	99W XL	654	233	7J	320 A A	E	B	71dB	C1
225/65R16	100H/100V	698	228	6½J	320 A A	---	---	---	---
235/65R16	103H	712	240	7J	320 A A	---	---	---	---
205/40ZR17	84W XL	596	212	7½J	320 A A	E	B	71dB	C1
205/45ZR17	88W XL	616	206	7J	320 A A	C	B	71dB	C1
205/50ZR17	93W XL	638	214	6½J	320 A A	C	B	71dB	C1
205/55ZR17	95W XL	658	214	6½J	320 A A	---	---	---	---
215/40ZR17	87W XL	604	218	7½J	320 A A	E	B	71dB	C1
215/45ZR17	91W XL	626	213	7J	320 A A	C	B	71dB	C1
215/50ZR17	95W XL	648	226	7J	320 A A	C	B	71dB	C1
215/55ZR17	98W XL	668	226	7J	320 A A	C	B	71dB	C1
225/45ZR17	94W XL	634	225	7½J	320 A A	E	B	71dB	C1
225/50ZR17	98W XL	658	233	7J	320 A A	C	B	71dB	C1
225/55ZR17	101W XL	680	233	7J	320 A A	C	B	71dB	C1
225/60R17	99H/99V	702	228	6½J	320 A A	---	---	---	---
235/45ZR17	97W XL	644	236	8J	320 A A	E	B	71dB	C1
235/50ZR17	96W	668	245	7½J	320 A A	---	---	---	---
235/50ZR17	100W XL	668	245	7½J	320 A A	---	---	---	---
235/55ZR17	103W XL	690	245	7½J	320 A A	C	B	71dB	C1
235/60R17	102H/102V	714	240	7J	320 A A	---	---	---	---
245/40ZR17	95W XL	628	248	8½J	320 A A	---	---	---	---
245/45ZR17	99W XL	652	243	8J	320 A A	E	B	71dB	C1
215/35ZR18	84W XL	607	218	7½J	320 A A	E	B	71dB	C1
215/40ZR18	89W XL	629	218	7½J	320 A A	---	---	---	---
225/40ZR18	92W XL	637	230	8J	320 A A	E	B	71dB	C1
225/45ZR18	95W XL	659	225	7½J	320 A A	C	B	71dB	C1
225/55ZR18	102W XL	705	233	7J	320 A A	---	---	---	---
235/40ZR18	95W XL	645	241	8½J	320 A A	E	B	71dB	C1
235/45ZR18	98W XL	669	236	8J	320 A A	E	B	71dB	C1
235/50ZR18	101W XL	693	245	7½J	320 A A	C	B	71dB	C1
235/55ZR18	104W XL	715	245	7½J	320 A A	C	B	71dB	C1
245/40ZR18	97W XL	653	248	8½J	320 A A	E	B	71dB	C1
245/45ZR18	100W XL	677	243	8J	320 A A	C	B	71dB	C1
245/50ZR18	100W	703	253	7½J	320 A A	---	---	---	---
255/35ZR18	94Y XL	635	260	9J	320 A A	E	B	72dB	C1
255/40ZR18	99W XL	661	260	9J	320 A A	---	---	---	---
255/45ZR18	103W XL	687	255	8½J	320 A A	C	B	72dB	C1
255/55R18	109V/109H XL	737	265	8J	320 A A	---	---	---	---
265/35ZR18	97Y XL	643	271	9½J	320 A A	E	B	72dB	C1
225/30ZR19	84W XL	619	230	8J	320 A A	---	---	---	---
225/35ZR19	88W XL	641	230	8J	320 A A	E	B	71dB	C1
235/35ZR19	91W XL	647	241	8½J	320 A A	E	B	71dB	C1
235/45ZR19	99W XL	695	236	8J	320 A A	---	---	---	---
245/35ZR19	93W XL	655	248	8½J	320 A A	E	B	71dB	C1
245/40ZR19	98W XL	679	248	8½J	320 A A	---	---	---	---
245/45ZR19	102W XL	703	243	8J	320 A A	C	B	71dB	C1
255/35ZR19	96W XL	661	260	9J	320 A A	---	---	---	---
255/40ZR19	100W XL	687	260	9J	320 A A	---	---	---	---
225/35ZR20	90W XL	666	230	8J	320 A A	E	B	71dB	C1
235/35ZR20	92W XL	672	241	8½J	320 A A	E	B	71dB	C1
245/35ZR20	95Y XL	680	248	8½J	320 A A	E	B	71dB	C1
255/35ZR20	97W XL	686	260	9J	320 A A	---	---	---	---
265/45ZR20	108W XL	746	266	9J	320 A A	---	---	---	---
265/50ZR20	111V XL	774	277	8½J	320 A A	C	B	72dB	C1
275/40ZR20	106W XL	728	278	9½J	320 A A	E	B	72dB	C1



SP766

ALL SEASON SUV TIRE H/T



Product features



Four wide grooves design provide effective drainage and sufficient wet safety performance.



Design of central rib with sipes promotes the rigidity, help to balance high-speed performance and grip performance on wet land.



The compact shoulder design provide excellent handling performance with low noise.



Multiple blade groove pattern provide excellent grip and handling performance on wet land.

Performance Test



Safety



Drainage



Low Noise



Grip



Handling



SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O. D (MM)	S. W (MM)	Standard Rim	U.T.Q.G					
215/75R15	100T	703	216	6J	440 AA	E	C	71dB	C1	
225/75R15	102T	719	223	6J	440 AA	E	C	71dB	C1	
235/75R15	105S	733	235	6½J	440 AA					
215/65R16	98H	686	221	6½J	440 AA					
215/70R16	100T	708	221	6½J	440 AA	E	C	71dB	C1	
225/70R16	103T	722	228	6½J	440 AA	E	C	71dB	C1	
235/60R16	100H/100V	688	240	7J	440 AA	E	C	71dB	C1	
235/65R16	103T/103H	712	240	7J	440 AA					
235/70R16	106T	736	240	7J	440 AA	E	C	71dB	C1	
245/70R16	107T	750	248	7J	440 AA	E	C	71dB	C1	
255/65R16	109H	738	260	7½J	440 AA	E	C	72dB	C1	
255/70R16	111T	764	260	7½J	440 AA	E	C	72dB	C1	
265/70R16	112T	778	272	8J	440 AA	E	C	72dB	C1	
275/70R16	114T/114H	792	279	8J	440 AA	E	C	72dB	C1	
215/60R17	96H	690	221	6½J	440 AA	E	C	71dB	C1	
215/65R17	99H	712	221	6½J	440 AA					
225/60R17	99H	712	221	6½J	440 AA					
225/65R17	102H	724	228	6½J	440 AA					
225/65R17	106H XL	724	228	6½J	440 AA	C	C	72dB	C1	
235/55R17	103V XL	690	245	7½J	440 AA	E	C	72dB	C1	
235/65R17	108H XL	738	240	7J	440 AA	C	C	72dB	C1	
245/65R17	111H XL	750	248	7J	440 AA	C	C	72dB	C1	
255/60R17	106V	738	260	7½J	440 AA	E	C	72dB	C1	
255/65R17	110T/110H	764	260	7½J	440 AA					
265/65R17	112H	776	272	8J	440 AA	E	C	72dB	C1	
265/65R17	116H XL	776	272	8J	440 AA	C	C	73dB	C1	
245/70R17	110T/110H	776	248	7J	440 AA					
265/70R17	115T/115H	804	272	8J	440 AA	C	C	72dB	C1	
285/65R17	116H	802	292	8½J	440 AA	E	C	74dB	C1	
225/60R18	100H	727	228	6½J	440 AA					
235/55R18	104V XL	715	245	7½J	440 AA	E	C	72dB	C1	
255/55R18	109V XL	737	265	8J	440 AA	E	C	73dB	C1	
235/60R18	107H XL	739	240	7J	440 AA					
235/65R18	110H XL	763	240	7J	440 AA					
245/60R18	105H/105V	751	248	7J	440 AA					
255/60R18	112H/112V XL	763	260	7½J	440 AA					
265/60R18	110H	775	272	8J	440 AA	E	C	72dB	C1	
265/65R18	114H	801	272	8J	440 AA					
265/70R18	116T	829	272	8J	440 AA					
275/65R18	116H	815	279	8J	440 AA	E	C	72dB	C1	
235/50R19	99V	719	245	7½J	440 AA					
245/55R19	103V	753	253	7½J	440 AA					
255/50R19	103V	739	265	8J	440 AA					
255/50R19	107V XL	739	265	8J	440 AA					
255/55R19	111H/111V XL	763	265	8J	440 AA					
265/50R19	110V XL	749	277	8½J	440 AA					
275/45R19	108V XL	731	273	9J	440 AA					
275/55R19	111V	785	284	8½J	440 AA					
285/50R20	116V XL	794	297	9J	440 AA	C	C	75dB	C1	
205/70R15	100T XL	669	209	6J	440 AA	E	C	72dB	C1	
255/70R15	108T	739	260	7½J	440 AA					
265/70R15	112T/112S	753	272	8J	440 AA					



SP786

ALL SEASON SUV TIRE A/T

Product features



Chamfer design of the pattern:
Prevent stone nipped, enhance the ability to get rid of the stone



Wide shoulder pattern design:
Enhance the block rigidity, endurance, weight-carrying ability and steering qualities during driving.



Staggered central rib design:
Solid staggered central rib design ensures straight-line driving stability and safety.



Multi-steel strap design:
Promote the grip performance on wet and dry land, enhance the tractive performance

Performance Test



SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O. D (MM)	S. W (MM)	Standard Rim	U.T.Q.G					
215R15C	113/111S-8PR	724	218	6J	480 AB	E	E	73dB	C2 TRACTION	
215/75R15LT	100/97Q-6PR	709	216	6J	480 AB	E	E	73dB	C2 TRACTION	
215/75R15LT	100/97R-6PR	709	216	6J	480 AB	E	E	73dB	C2 TRACTION	
225/75R15LT	108/104Q-8PR	725	223	6J	480 AB	E	E	73dB	C2 TRACTION	
225/75R15LT	108/104R-8PR	725	223	6J	480 AB	E	E	73dB	C2 TRACTION	
235/75R15LT	116/113Q-10PR	739	235	6½J	480 AB	E	E	73dB	C2 TRACTION	
235/75R15LT	116/113R-10PR	739	235	6½J	480 AB	E	E	73dB	C2 TRACTION	
30×9.50R15LT	104Q-6PR	756	240	7½J	480 AB	E	C	73dB	C2 TRACTION	
31×10.50R15LT	109R-6PR	781	268	8½J	480 AB	E	C	73dB	C2 TRACTION	
31×10.50R15LT	109S-6PR	781	268	8½J	480 AB	E	C	73dB	C2 TRACTION	
205R16C	110/108S-8PR	736	208	6J	480 AB	E	E	73dB	C2 TRACTION	
215/70R16	100S	708	221	6½J	480 AB					
215/70R16	100T	708	221	6½J	480 AB					
215/85R16LT	110/107Q-8PR	778	216	6J	480 AB	E	E	73dB	C2 TRACTION	
215/85R16LT	110/107R-8PR	778	216	6J	480 AB	E	E	73dB	C2 TRACTION	
215/85R16LT	115/112Q-10PR	778	216	6J	480 AB	E	E	73dB	C2 TRACTION	
215/85R16LT	115/112R-10PR	778	216	6J	480 AB	E	E	73dB	C2 TRACTION	
225/70R16	103S	722	228	6½J	480 AB					
225/70R16	103T	722	228	6½J	480 AB					
225/75R16LT	115/112Q-10PR	750	223	6J	480 AB	E	E	73dB	C2 TRACTION	
225/75R16LT	115/112R-10PR	750	223	6J	480 AB	E	E	73dB	C2 TRACTION	
235/70R16	106S	736	240	7J	480 AB					
235/70R16	106T	736	240	7J	480 AB					
235/85R16LT	120/116Q-10PR	812	235	6½J	480 AB	E	E	73dB	C2 TRACTION	
235/85R16LT	120/116R-10PR	812	235	6½J	480 AB	E	E	73dB	C2 TRACTION	
245/70R16	107S	750	248	7J	480 AB					
245/70R16	107T	750	248	7J	480 AB					
245/75R16LT	120/116Q-10PR	780	248	7J	480 AB	E	E	73dB	C2 TRACTION	
245/75R16LT	120/116R-10PR	780	248	7J	480 AB	E	E	73dB	C2 TRACTION	
255/70R16	111S	764	260	7½J	480 AB					
255/70R16	111T	764	260	7½J	480 AB					
265/70R16	112S	778	272	8J	480 AB					
265/70R16	112T	778	272	8J	480 AB					
265/70R16LT	121/118R-10PR	784	272	8J	480 AB	E	C	73dB	C2 TRACTION	
265/70R16LT	121/118S-10PR	784	272	8J	480 AB	E	C	73dB	C2 TRACTION	
265/75R16LT	123/120Q-10PR	810	267	7½J	480 AB	E	C	75dB	C3 TRACTION	
265/75R16LT	123/120R-10PR	810	267	7½J	480 AB	E	C	75dB	C3 TRACTION	
275/70R16	114S	792	279	8J	480 AB					
275/70R16	114T	792	279	8J	480 AB					
285/75R16LT	126/123Q-10PR	840	286	8J	480 AB	E	C	75dB	C3 TRACTION	
285/75R16LT	126/123R-10PR	840	286	8J	480 AB	E	C	75dB	C3 TRACTION	
235/80R17LT	120/117Q-10PR	814	235	6½J	480 AB	E	E	73dB	C2 TRACTION	
235/80R17LT	120/117R-10PR	814	235	6½J	480 AB	E	E	73dB	C2 TRACTION	
245/70R17LT	119/116R-10PR	782	248	7J	480 AB	E	E	73dB	C2 TRACTION	
245/70R17LT	119/116S-10PR	782	248	7J	480 AB	E	E	73dB	C2 TRACTION	
245/75R17LT	121/118Q-10PR	806	248	7J	480 AB	E	E	73dB	C2 TRACTION	
245/75R17LT	121/118R-10PR	806	248	7J	480 AB	E	E	73dB	C2 TRACTION	
265/65R17	112S	776	272	8J	480 AB					
265/65R17	112T	776	272	8J	480 AB					
265/70R17	115S	804	272	8J	480 AB					
265/70R17	115T	804	272	8J	480 AB					
265/70R17LT	121/118R-10PR	810	272	8J	480 AB	E	C	73dB	C2 TRACTION	
265/70R17LT	121/118S-10PR	810	272	8J	480 AB	E	C	73dB	C2 TRACTION	
275/65R17	115S	790	279	8J	480 AB					
275/65R17	115T	790	279	8J	480 AB					
285/70R17LT	121/118R-8PR	838	292	8½J	480 AB	E	C	73dB	C2 TRACTION	
285/70R17LT	121/118S-8PR	838	292	8½J	480 AB	E	C	73dB	C2 TRACTION	
265/70R18LT	124/121R-10PR	829	272	8J	480 AB	E	C	75dB	C3 TRACTION	
265/70R18LT	124/121S-10PR	829	272	8J	480 AB	E	C	75dB	C3 TRACTION	
275/65R18LT	123/120S-10PR	821	279	8J	480 AB	E	C	75dB	C3 TRACTION	



Innovative Technology



SP796

COMMERCIAL TIRE VAN



Performance Test



SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O. D (MM)	S. W (MM)	Standard Rim	U.T.Q.G				
175/65R14C	90/88T-6PR	584	177	5J	---	---	---	---	---
185R14C	102/100S-8PR	650	188	5½J	---	C	E	72dB	C2
195R14C	106/104S-8PR	666	198	5½J	---	C	E	72dB	C2
205R14C	109/107R-8PR	684/686	208	6J	---	C	E	72dB	C2
215/75R14C	112/110R-8PR	678	216	6J	---	C	E	72dB	C2
195R15C	106/104S-8PR	693	196	5½J	---	C	E	72dB	C2
6.50R15C	106/101N-10PR	730	180	5.50F	---	---	---	---	---
7.00R15LT	109/105N-10PR	750	200	5.50F	---	---	---	---	---
6.50R16C	108/107N-10PR	750	185	4½J	---	C	E	72dB	C2
7.00R16C	117/116N-12PR	775	200	5½J	---	C	E	72dB	C2
7.50R16C	121/120N-12PR	805	215	6.00G	---	C	E	72dB	C2
195/70R15C	104/102S-8PR	655	201	6J	---	C	E	72dB	C2
205/70R15C	106/104S-8PR	669	209	6J	---	C	E	72dB	C2
215/70R15C	109/107S-8PR	683	221	6½J	---	C	E	72dB	C2
225/70R15C	112/110S-8PR	697	228	6½J	---	C	E	72dB	C2
175/75R16C	98/96Q-6PR	668	177	5J	---	C	E	72dB	C2
185/75R16C	104/102S-8PR	684	184	5J	---	C	E	72dB	C2
195/60R16C	99/97T-6PR	640	201	6J	---	C	E	72dB	C2
195/65R16C	104/102T-8PR	660	201	6J	---	C	E	72dB	C2
195/75R16C	107/105S-8PR	698	196	5½J	---	C	E	72dB	C2
205/65R16C	107/105T-8PR	672	209	6J	---	C	E	72dB	C2
205/75R16C	110/108R-8PR	714	203	5½J	---	C	E	72dB	C2
215/60R16C	103/101T-6PR	664	221	6½J	---	C	E	72dB	C2
215/65R16C	109/107T-8PR	686	221	6½J	---	C	E	72dB	C2
215/75R16C	113/111S-8PR	728	216	6J	---	---	---	---	---
215/75R16C	116/114R-10PR	728	216	6J	---	C	E	72dB	C2
225/65R16C	112/110T-8PR	698	228	6½J	---	C	E	72dB	C2
225/75R16C	116/114S-8PR	744	223	6J	---	---	---	---	---
225/75R16C	121/120R-10PR	744	223	6J	---	C	E	72dB	C2
235/65R16C	115/113T-8PR	712	240	7J	---	C	E	72dB	C2




SP788

UHP TIRE



Product features



"Flying wing type" high gradient of single-oriented symmetrical pattern design, giving the tire super visual sense of speed, drainage performance and curve control.



Four wide and deep longitudinal groove design, giving the tire excellent wetland drainage performance and handling stability.



Central wide rib design, ensuring the steering performance.



Variable width of the groove design can effectively avoid airflow frequency vibration, prevent entrained gravel, reduce abnormal wear and improve the tire service life.

Performance Test



SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O. D (MM)	S. W (MM)	Standard Rim	U.T.Q.G	
255/45ZR17	98W	662	255	8½J	320AA	---
255/45R17	98V	662	255	8½J	320AA	---
235/45ZR18	98W XL	669	236	8J	320AA	---
255/40ZR18	99W XL	661	260	9J	320AA	---
235/55ZR19	105W XL	741	245	7½J	320AA	---
245/35ZR19	93W XL	655	248	8½J	320AA	---
245/45ZR19	102W XL	703	243	8J	320AA	---
245/55ZR19	103W	753	253	7½J	320AA	---
265/30ZR19	93W XL	643	271	9½J	320AA	---
235/30ZR20	88W XL	651	241	8½J	320AA	---
245/35ZR20	95W XL	680	248	8½J	320AA	---
245/45ZR20	103W XL	728	243	8J	320AA	---
245/50ZR20	102W	754	253	7½J	320AA	---
255/45ZR20	105W XL	738	255	8½J	320AA	---
255/50ZR20	109Y XL	764	265	8J	320AA	---
255/50ZR20	109W XL	764	265	8J	320AA	---
265/40ZR20	104Y XL	720	271	9½J	320AA	---
265/50ZR20	111W XL	774	277	8½J	320AA	---
275/35ZR20	102W XL	700	278	9½J	320AA	---
275/40ZR20	106W XL	728	278	9½J	320AA	---
275/40R20	106V XL	728	278	9½J	320AA	---
275/45ZR20	110W XL	756	273	9J	320AA	---
275/55R20	117V XL	810	284	8½J	320AA	---
275/55ZR20	117W XL	810	284	8½J	320AA	---
285/50ZR20	116W XL	794	297	9J	320AA	---
225/30ZR22	86W XL	695	230	8J	320AA	---
235/30ZR22	90W XL	701	241	8½J	320AA	---
245/30ZR22	92W XL	707	248	8½J	320AA	---
255/30ZR22	95W XL	713	260	9J	320AA	---
265/30ZR22	97W XL	719	271	9½J	320AA	---
265/35ZR22	102W XL	745	271	9½J	320AA	---
265/40ZR22	106W XL	771	271	9½J	320AA	---
285/35ZR22	106W XL	759	290	10J	320AA	---
285/45ZR22	114W XL	815	285	9½J	320AA	---
295/25ZR22	97Y XL	707	301	10½J	320AA	---
295/30ZR22	103W XL	737	301	10½J	320AA	---
305/40ZR22	114W XL	803	313	11J	320AA	---
305/45ZR22	118W XL	833	303	10J	320AA	---
255/30ZR24	97W XL	764	260	9J	320AA	---
275/25ZR24	96W XL	748	283	10J	320AA	---
275/30ZR24	101W XL	776	278	9½J	320AA	---
295/35R24	110V XL	816	301	10½J	320AA	---
295/35ZR24	110W XL	816	301	10½J	320AA	---




SP7866


UHP TIRE / RUN-FLAT TIRE




Product features




Smooth asymmetric pattern, ensuring better controlling performance of outside while enhancing drainage of inside



Four wide and deep longitudinal groove design, giving the tire excellent wetland drainage performance and handling stability.



Outside shoulder reinforcement improving handling performance at curve, effectively preventing abnormal wear.



Bended steel groove, effectively reducing the noise while enlarging ground contact area.

Performance Test



UHP TIRE SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O.D (MM)	S.W (MM)	Standard Rim	U.T.Q.G		
245/45ZR17	99W XL	652	243	8J	320AA	---	---
235/45ZR18	98W XL	669	236	8J	320AA	---	---
275/40ZR18	99Y	677	278	9½J	320AA	---	---
225/45ZR19	96W XL	685	225	7½J	320AA	---	---
255/45ZR19	104W XL	713	255	8½J	320AA	---	---
285/40ZR19	103Y	711	290	10J	320AA	---	---
285/40ZR19	107Y	711	290	10J	320AA	---	---
245/45ZR20	103W XL	728	243	8J	320AA	---	---
255/40ZR20	101W XL	712	260	9J	320AA	---	---
265/40ZR20	104W XL	720	271	9½J	320AA	---	---
275/40ZR20	106W XL	728	278	9½J	320AA	---	---
275/40R20	106V XL	728	278	9½J	320AA	---	---

RUN-FLAT TIRE SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O.D (MM)	S.W (MM)	Standard Rim	U.T.Q.G		
225/50ZRF17	98W XL	658	233	7J	320AA	---	---
225/55ZRF17	101W XL	680	233	7J	320AA	---	---
225/45ZRF18	95W XL	659	225	7½J	320AA	---	---
245/45ZRF18	100W XL	677	243	8J	320AA	---	---
245/50ZRF18	100W	703	253	7½J	320AA	---	---
255/40ZRF18	99W XL	661	260	9J	320AA	---	---
255/55RF18	109V XL	737	265	8J	320AA	---	---
255/55ZRF18	109W XL	737	265	8J	320AA	---	---
255/50RF19	107V XL	739	265	8J	320AA	---	---
255/50ZRF19	107W XL	739	265	8J	320AA	---	---



SP718

TAXI PATTERN TIRE



Product features



Advanced structure design:

Using new type nylon cap layer which is intact and no joints, effectively prevent belt from sliding, provide perfect stability performance even in the status of turning at high speed.



Excellent wear-resistance compound technology

Optimized wear-resistance compound make tires to be suitable for rough road, longer mileage, energy saving and Eco-friendly.

Performance Test



SP718 SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O. D (MM)	S. W (MM)	Standard Rim	U.T.Q.G	Icons
155R13C	85/83S 6PR	578	157	4½J	460AA	---
155/65R13	73T/73H	532	157	4½J	460AA	---
165R13C	91/89S 6PR	596	167	4½J	460AA	---
165/65R13	77T	544	170	5.00B	460AA	---
165/70R13	79T	562	170	5.00B	460AA	---
165/70R13C	88/86S 6PR	562	170	5J	460AA	---
175/60R13	77H	540	177	5J	460AA	---
175/70R13	82T	576	177	5.00B	460AA	---
185/70R13	86T	590	189	5.50B	460AA	---
165/60R14	75H	554	170	5J	460AA	---
165/70R14	81H	588	170	5J	460AA	---
175/65R14	82H	584	177	5J	460AA	---
175/70R14	84T	602	177	5J	460AA	---
175/70R14LT	95/93S	602	177	5J	460AA	---
175/75R14C	99/98S	618	177	5J	460AA	---
185/60R14	82H	578	189	5½J	460AA	---
185/65R14	86H	596	189	5½J	460AA	---
185/70R14	88T	616	189	5½J	460AA	---
185/80R14	91T	652	184	5J	460AA	---
185R14C	102/100T 8PR	650	188	5½J	460AA	---
185R14LT	102/100T 8PR	650	188	5½J	460AA	---
195/60R14	86H	590	201	6J	460AA	---
195/70R14	91H	630	201	6J	460AA	---
195R14C	106/104S 8PR	666	198	5½J	460AA	---
195R14LT	105/103S 8PR	666	198	5½J	460AA	---
205/70R14	95H	644	209	6J	460AA	---
175/65R15	84H	609	177	5J	460AA	---
185/60R15	84/88H	603	189	5½J	460AA	---
185/65R15	88H	621	189	5½J	460AA	---
195/60R15	88H	615	201	6J	460AA	---
195/65R15	91H	635	201	6J	460AA	---



SP701

COMMERCIAL TIRE VAN

Performance Test



SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O. D (MM)	S. W (MM)	Standard Rim	U.T.Q.G	
155R12C	88/86N-8PR	553	157	4.50B	--	--



MUD HUNTER

Product features

Block block shoulder design increases the intensity of the pattern. The high and low shoulder and the inside and outside shoulder are interlaced to greatly improve the passing performance. The interlaced middle block and different design on both side improve the cross-country performance. Fearless road conditions, professional MT tire



Performance Test



SP702

COMMERCIAL TIRE VAN

Performance Test



SIZE RANGE

SIZE	LOAD INDEX & SPEED RATING	O. D (MM)	S. W (MM)	Standard Rim	U.T.Q.G	
185R14C	102/100Q-8PR	650	188	5½J	--	--
195R14C	105/103Q-8PR	666	198	5½J	--	--
185R15C	98/97Q-6PR	677	189	5½J	--	--
195R15C	106/104-8PRQ	693	196	5½J	--	--

SIZE	LOAD INDEX / SPEED RATING	STANDARD RIM	MAX.LOAD(kg)	MAX.PRESSURE(kpa)
35*12.5R17LT	121Q	10.0J	1450	450
33*12.5R18LT	118Q	10.0J	1320	450
35*12.5R18LT	123Q	10.0J	1550	450
LT235/75R15	116/113Q 110/107Q	6.5J	1250/1150	550
30×9.50R15LT	104Q	7.5J	900	350
31×10.50R15LT	109Q	8.5J	1030	350
LT245/75R16	120/116Q 114/111Q	7.0J	1380/1260	550
LT265/75R16	123/120Q 119/116Q	7.5J	1550/1400	550
LT285/75R16	126/123Q	8.0J	1700/1550	550
LT265/70R17	121/118Q	8.0J	1450/1320	550
LT285/70R17	121/118Q	8.5J	1450/1320	550
33×12.50R20LT	114Q	10.0J	1180	450
35×12.50R20LT	121Q	10.0J	1450	450

RACE TIRE

SIZE	LOAD INDEX & SPEED RATING	O. D (MM)	S. W (MM)	Standard Rim	U.T.Q.G	
195/50R15	82V	577	201	6J	180AA	---
205/45ZR17	88W XL	616	206	7J	180AA	---
215/45ZR17	91W XL	626	213	7J	180AA	---
225/50ZR17	98W XL	658	233	7J	180AA	---
245/45ZR18	100W XL	677	243	8J	180AA	---

NEW.SPORT.DESIGN
Swift as the lightning

Excellent road grip and safety when cornering,
 new type of 3D groove and innovative tread technology.

TIRE FEATURES WITH CARBON NANO-TUBES COMPOUND

- 1.Low rolling resistance,more fuel-efficient eco-friendly
- 2.No static,more safety
- 3.High speed performance
- 4.Lower tread temperature and longer service life

SPORTRAK
just run just win

**SEEK FOR EXCELLENT QUALITY
 CAST ON PERFECT TIRES**

**CARBON NANO-TUBES TIRE
 THE GREEN REVOLUTION**

The tire's comprehensive performance got greatly improved by using carbon nano-tubes material

TIRE FEATURES WITH CARBON NANO-TUBES COMPOUND

- 1.Low rolling resistance,more fuel-efficient eco-friendly
- 2.No static,more safety
- 3.High speed performance
- 4.Lower tread temperature and longer service life



CARBON NANO-TUBES
 COMPOUND IDENTIFYING