



SPORTRAK
— just run just win —

www.miaitireinternational.com



**SPORTRAK
TIRE**

SPORTRAK
— just run just win —



SP301



- ◇ Suitable for all wheel positions of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- ◇ 4 linear grooves design provides excellent directional driving performance and prevents uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
225/70R19.5	6.75	14PR	128/126	M	13	1800/1700	760
245/70R19.5	7.50	16PR	135/133	L	13	2180/2060	830
265/70R19.5	7.50	16PR	143/141	J	13	2727/2575	850
295/60R22.5	9.00	18PR	150/147	K	16	3350/3075	900
315/70R22.5	9.00	18PR	151/148	M	14.5	3450/3150	830



SP302



- ◇ Suitable for all wheel positions of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- ◇ 4 linear grooves design provides excellent directional driving performance and prevents uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
8R17.5	6.00	12PR	122/120	J	13	1500/1400	760
215/75R17.5	6.00	16PR	135/133	L	13	2180/2060	860
235/75R17.5	6.75	16PR	143/141	L	13	2725/2527	860
255/70R22.5	7.50	16PR	140/137	N	10.5	2500/2300	830
275/70R22.5	8.25	16PR	148/145	M	13	3150/2900	900



SP303



- ◇ Used for driving wheel
- ◇ Widened tread design, can increase the contact area of tread and ground grasping capacity
- ◇ Transverse pattern design, supply good self-cleaning

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
295/60R22.5	9.00	18PR	150/147	K	19	3350/3075	900
315/70R22.5	9.00	18PR	151/148	M	19	3450/3150	830



SP304



- ◇ Vertical deep groove design can provide excellent driving and braking force.
- ◇ The steel cord tire with high density. Good wear-resistant, high traction power. High load capacity.
- ◇ Can be used for mixed road condition.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
315/80R22.5	9.00	20PR	157/154	J	23.5	4125/3750	900



SP305



- ◇ Suitable for driving wheel position of middle/long distance trucks on better road conditions.
- ◇ Directional mixed pattern design provides extremely good traction and prevents hydroplaning.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
225/70R19.5	6.75	14PR	128/126	L	15	1800/1700	760
245/70R19.5	7.50	14PR	133/131	L	15	2060/1950	760
265/70R19.5	7.50	16PR	143/141	J	17.5	2727/2575	850



SP306



- ◇ New low heat tire shoulder designed to provide excellent high-speed performance
- ◇ Widened tread design effectively increases the wear volume and extends tire life
- ◇ New design of tread provides excellent wear resistance
- ◇ Optimized tread design effectively reduces rolling resistance
- ◇ Special design provide self cleaning function
- ◇ Unique tire shape and strong steel cord structure providing excellent durability performance

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
425/65R22.5	13.00	20PR	165	K	18	5150	830
445/65R22.5	13.00	20PR	168	L	18	5600	830



SP307



- ◇.Suitable for all position of trucks running on/off road.
- ◇.High traction

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
14.00R20	10.00	18PR	161/158	K	20	4625/4250	690
7.50R16LT	6.00G	8 PR	122/118	M	15	1500/1320	770



SP310



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
6.50R16LT	5.5F	12PR	110/105	M	9.5	1060/925	670
7.00R16LT	5.5F	14PR	118/114	M	11	1320/1180	770



SP308



- ◇.Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions
- ◇.4 linear grooves design provides excellent directional driving performance and prevent uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9R22.5	6.75	14PR	136/134	L	14.5	2240/2120	760
10R22.5	7.50	16PR	144/142	M	15	2800/2650	790



SP311



- ◇.Used for driving wheel
- ◇.Widen tread design, can increase the contact area of tread and ground grasping capacity
- ◇.Transverse pattern design, supply good self-cleaning

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
215/75R17.5	6.00	18PR	135/133	J	12.5	2180/2060	850



SP309



- ◇.Suitable for all position of trucks running on/off road.
- ◇.High traction

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
14.00R20	10.00	20PR	164/161	J	20	5000/4625	790



SP312



- ◇.Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions
- ◇.4 linear grooves design provides excellent directional driving performance and prevent uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
275/80R22.5	8.25	16PR	149/146	L	14.5	3000/2725	830
295/80R22.5	9.00	18PR	152/149	M	14.5	3550/3250	900



SP313



- ◇.Used for driving wheel
- ◇.For good road and mixed road condition
- ◇.Widen tread design ,can increase tread contact area and ground grasping capacity

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
295/75R22.5	9.00	14PR	144/141	L	23	2800/2575	760



SP335/BYA991



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
6.50R16LT	5.5F	12PR	110/105	K	10.5	1060/925	670
7.00R16LT	5.5F	14PR	118/114	K	11.5	1320/1180	770



SP314



- ◇.The four vertical zigzag pattern groove design offers good traction and brake
- ◇.Special shoulder groove design reduce it's temperature
- ◇.Line of the groove takes special structure,which can keep tire clean from the stone effectively

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
385/55R22.5	12.25	20PR	160	K	15.5	4500	900



SP366



- ◇.Drive axle for on/off road conditions
- ◇.Deep and rigid block design for long life and good traction
- ◇.Cut resistance compound

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
6.50R16LT	5.5F	10PR	107/102	L	9.7	975/850	560
7.00R16LT	5.5F	12PR	115/110	M	9.7	1215/1060	670
7.50R16LT	6.0G	14PR	122/118	L	10.5	1500/1320	770



SP328 / SP328C/SP328L SP328G/SP328G+



- ◇.Suitable for all wheels
- ◇.Good traction and braking performance
- ◇.Good durability, anti-puncturing
- ◇.Applied to road with good even poor conditions

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.00R16LT	5.5F	14PR	118/114	M	11	1320/1180	770
12.00R20	8.5	18PR	154/151	K	16	3750/3450	830
	8.5	20PR	156/153	K	16	4000/3650	900
12.00R24	8.5	20PR	160/157	K	15.5	4500/4125	900
315/80R22.5	9.00	20PR	157/154	K	15	4125/3750	830



SP395



- ◇.New low heat tire shoulder designed to provide excellent high-speed performance
- ◇.Widened tread design effectively increases the wear volume and extends tire life
- ◇.New design of tread provides excellent wear resistance
- ◇.Optimized tread design effectively reduces rolling resistance
- ◇.Special design provide self cleaning function
- ◇.Unique tire shape and strong steel cord structure providing excellent durability performance

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
385/65R22.5	11.75	20PR	160	K	16	4500	900



SP396



- ◇.New low heat tire shoulder designed to provide excellent high-speed performance
- ◇.Widened tread design effectively increases the wear volume and extends tire life
- ◇.New design of tread provides excellent wear resistance
- ◇.Optimized tread design effectively reduces rolling resistance
- ◇.Special design provide self cleaning function
- ◇.Unique tire shape and strong steel cord structure providing excellent durability performance

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
385/65R22.5	11.75	20PR	160	K	16	4500	900



SP398/BYS98



- ◇.Excellent load capacity and high speed capacity
- ◇.Good wear-resistant, high traction power, excellent anti-puncture
- ◇.Suitable for all kinds of road conditions

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	17.0	3450/3150	930
12R22.5	9.00	18PR	152/149	K	17.0	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	17.0	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	17.0	4125/3750	900



SP639/BYS695



- ◇.vertical groove patten design stops anti-slip effectively, and offer excellent handling performance
- ◇.safe and advanced pattern design reduce rolling resistance , and ensure tire fuel economy and high speed performance
- ◇.latest anti-wear formulation ensure excellent anti-wear performance

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
285/75R24.5	8.25	16PR	147/144	M	15.5	3075/2800	830
295/75R22.5	9.00	16PR	146/143	M	15.5	3000/2725	830
11R22.5	8.25	16PR	146/143	M	15.5	3000/2725	830
11R24.5	8.25	16PR	149/146	M	15.5	3250/3000	830



SP831/BYT691



- ◇.Special desgin for uni-skidding and perfect handling
- ◇.Central tread ensure excellent gripping and reduce rolling resistance
- ◇.Unique technical formula improve the wear-resistance and stability

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
285/75R24.5	8.25	16PR	147/144	M	10.5	3075/2800	830
295/75R22.5	9.00	16PR	146/143	M	10.5	3000/2725	830
11R22.5	8.25	16PR	146/143	M	10.5	3000/2725	830
11R24.5	8.25	16PR	149/146	M	10.5	3250/3000	830



SP901/BS28



- ◇.Suitable for all wheels
- ◇.Good traction and braking performance
- ◇.Good durability, anti-puncturing
- ◇.Suitable for good and bad road conditions

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.50R16LT	6.00G	14PR	122/118	K	12.0	1500/1320	770
8.25R16LT	6.50H	16PR	128/124	K	13.0	1800/1600	770
8.25R20	6.5	16PR	139/137	K	15.5	2430/2300	900
9.00R20	7.0	16PR	144/142	K	15.5	2800/2650	900
10.00R20	7.5	18PR	149/146	K	16.5	3250/3000	930
11.00R20	8.0	18PR	152/149	K	17.0	3550/3250	930
12.00R20	8.5	20PR	156/153	K	17.5	4000/3650	900
12.00R24	8.5	20PR	160/157	K	17.5	4500/4125	900
11R22.5	8.25	18PR	151/148	K	15.5	3450/3150	930
12R22.5	9.00	18PR	152/149	K	15.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	15.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	15.5	3550/3250	900



SP905/BYA685W



- ◇.New tubeless tyre pattern
- ◇.Good traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
385/65R22.5	11.75	20PR	160	K	16	4500	900



SP902/BYD68



- ◇.Used for driving wheel
- ◇.Widen tread design, can increase the contact area of tread and ground grasping capacity
- ◇.Transverse pattern design, supply good self-cleaning

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	18.5	3450/3150	930
12R22.5	9.00	18PR	152/149	K	18.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	18.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	18.5	4125/3750	900



SP907/BS18



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.50R16LT	6.00G	14PR	122/118	K	12.0	1500/1320	770
8.25R16LT	6.50H	16PR	128/124	K	13.0	1800/1600	770
10.00R20	7.5	18PR	149/146	K	16.0	3250/3000	930
11.00R20	8.0	18PR	152/149	K	16.5	3550/3250	930
12.00R20	8.5	18PR	154/151	K	17.5	3750/3450	830
	8.5	20PR	156/153	K	17.5	4000/3650	900
12.00R24	8.5	20PR	160/157	K	16.0	4500/4125	900



SP908/BS29



- ◇.With perfect driving performance, used for driving wheel
- ◇.Good ground grasping capability, excellent performance
- ◇.Suitable for rough road and mining road condition

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9.00R20	7.0	16PR	144/142	K	16.5	2800/2650	900
10.00R20	7.5	18PR	149/146	K	18.5	3250/3000	930
11.00R20	8.0	18PR	152/149	K	19.5	3550/3250	930
12.00R20	8.5	18PR	154/151	K	20.5	3750/3450	830
	8.5	20PR	156/153	K	20.5	4000/3650	900



SP906



- ◇.Specially designed for long distance transportation vehicles on good road conditions, suitable for all wheel positions of middle and long distance coach, steering wheel position of middle and long distance trucks.
- ◇.Comfortable and safer driving experience; longer mileage

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
315/80R22.5	9.00	20PR	157/154	K	14.5	4125/3750	830



SP909/BY06



- ◇.Sturdy tread pattern, suitable for bad road condition
- ◇.Supply excellent traction and driving power
- ◇.Ultra-deep tread depth improve 50% service life
- ◇.Open tire shoulder design, good heat dispersion and self-cleaning
- ◇.Good durability, anti-fatigue properties

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
10.00R20	7.5	18PR	149/146	G	18.0	3250/3000	930
11.00R20	8.0	18PR	152/149	G	20.5	3550/3250	930
12.00R20	8.5	18PR	154/151	G	22.5	3750/3450	830
	8.5	20PR	156/153	G	22.5	4000/3650	900
11R22.5	8.25	18PR	151/148	K	20.5	3450/3150	930
12R22.5	9.0	18PR	152/149	G	20.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	20.5	3750/3450	830
295/80R22.5	9.0	18PR	152/149	G	20.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	20.5	4125/3750	900



SP912/BY35



- ◇.Designed for construction and mining road, and short haul
- ◇.Special deep pattern improves the traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture
- ◇.Extra deep tread pattern can increase mileage 20%

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.50R16LT	6.00H	14PR	122/118	K	14.5	1500/1320	770
8.25R16LT	6.50H	16PR	128/124	K	15.0	1800/1600	770
8.25R20	6.5	16PR	139/137	K	16.5	2430/2300	930
9.00R20	7.0	16PR	144/142	K	16.5	2800/2650	900
10.00R20	7.5	18PR	149/146	K	18.5	3250/3000	930
11.00R20	8.0	18PR	152/149	K	20.5	3550/3250	930
12.00R20	8.5	18PR	154/151	J	21.5	3750/3450	830
	8.5	20PR	156/153	J	21.5	4000/3650	900



SP913



- ◇ Suitable for driving wheel position of vans on poor road conditions
- ◇ Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance
- ◇ Deeper tread pattern design offers enhanced tire mileage for better economy
- ◇ Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom, thereby resulting in a safer driving experience

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
315/80R22.5	9.00	20PR	157/154	K	17.5	4125/3750	830



SP917



- ◇ Sturdy tread pattern, suitable for bad road condition
- ◇ Supply excellent traction and driving power
- ◇ Ultra-deep tread depth improve 50% service life
- ◇ Open tire shoulder design, good heat dispersion and self-cleaning
- ◇ Good durability, anti-fatigue properties

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	20.5	3450/3150	930
12R22.5	9.00	18PR	152/149	K	20.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	20.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	20.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	20.5	4125/3750	900
275/70R22.5	8.25	16PR	148/145	M	20.5	3150/2900	900



SP915/BYD865



- ◇ Vertical deep groove design can provide excellent driving and braking force.
- ◇ The steel cord tire with high density. Good wear-resistant, high traction power. High load capacity.
- ◇ Can be used for mixed road condition.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11.00R20	8.0	18PR	152/149	G	20.5	3550/3250	930
12.00R20	8.5	20PR	156/153	G	22.5	4000/3650	900



SP920/BYD68+



- ◇ Excellent driving and braking force, good steering stability on muddy roads.
- ◇ For good roads and mixed road condition.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	18.5	3450/3150	900
12R22.5	9.00	18PR	152/149	K	18.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	18.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	18.5	4125/3750	900



SP916/BYA699C



- ◇ New tubeless tyre pattern
- ◇ Good traction and braking performance
- ◇ Reduce heat-producing, enhance the service durability
- ◇ Strengthened steel belts protect the tyre body from puncture

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	16.5	3450/3150	930
12R22.5	9.00	18PR	152/149	K	16.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	17.5	3750/3450	830



SP921/BYS98+



- ◇ Cross-winding groove tread design can reduce tire rolling resistance.
- ◇ Excellent ride comfort.
- ◇ Anti-skid, steering and excellent stability, low noise.
- ◇ Applicable to good road condition (highway).

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	17.0	3450/3150	930
12R22.5	9.00	18PR	152/149	K	17.0	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	17.0	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	17.0	4125/3750	900



SP922



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12.00R24	8.5	20PR	160/157	K	15	4500/4125	900



SP962/BYD983



- ◇.Designed for construction and mining road, and short haul
- ◇.Special deep pattern improves the traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture
- ◇.Extra deep tread pattern can increase mileage 20%

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.00R16LT	5.5F	12PR	115/110	K	16	1215/1060	670
	5.5F	14PR	118/114	K	16	1320/1180	770
12.00R24	8.5	20PR	160/157	K	18.5	4500/4125	900



SP928



SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9.5R17.5	6.75	18PR	143/141	J	14.5	2725/2575	875



SP965/BYD88



- ◇.Designed for construction and mining road, and short haul
- ◇.Special deep pattern improves the traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture
- ◇.Extra deep tread pattern can increase mileage 20%

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	18.0	3450/3150	930
12R22.5	9.00	18PR	152/149	K	18.0	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830



SP929



- ◇.Drive axle for on/off road conditions
- ◇.Deep and rigid block design for long life and good traction

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9.5R17.5	6.75	18PR	143/141	J	16.0	2725/2575	875



SP981



- ◇.Sturdy tread pattern, suitable for bad road condition
- ◇.Supply excellent traction and driving power
- ◇.Ultra-deep tread depth improve 50% service life
- ◇.Open tire shoulder design, good heat dispersion and self-cleaning
- ◇.Good durability, anti-fatigue properties

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12.00R24	8.5	20PR	160/157	K	18.5	4500/4125	900



SP997/BYD697



- ◇ Used for driving wheel
- ◇ For good road and mixed road condition
- ◇ Widen tread design ,can increase tread contact area and ground grasping capacity

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	16PR	146/143	L	20.5	3000/2725	830
11R24.5	8.25	16PR	149/146	L	20.5	3250/3000	830
285/75R24.5	8.25	16PR	147/144	L	20.5	3075/2800	830
295/75R22.5	9.00	16PR	146/143	L	20.5	3000/2725	830



BYD986



- ◇.Exclusive for drive, special tread prescription, reasonable groove design, offer excellent abrasion lifetime
- ◇.The wide tread design and block pattern, protect the tread,prolong the tire lifetime, improve the drive force and pressure

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12R22.5	9.00	18PR	152/149	K	24.5	3550/3250	930



BYT698C



- ◇.All new low heating shoulder prescription offer the excellent high-speed performance
- ◇.The wide tread design increase abrasion volume and prolong tyres life
- ◇.Long-distance wearable prescription make the high mileage
- ◇.The optimization tyre shape design, strong bead wire ring structure make the tyre have excellent durability

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
10.00R20	7.5	18PR	149/146	K	16.0	3250/3000	930
11.00R20	8.0	18PR	152/149	K	16.5	3550/3250	930
12.00R20	8.5	18PR	154/151	K	17.0	3750/3450	830
		20PR	156/153	J	17.0	4000/3650	900
12R22.5	9.00	18PR	152/149	K	18.5	3550/3250	930



BYD987



- ◇.Hot seasons, one-way can't exceed 150 kilometers
- ◇.Block pattern with deep tread depth design provide super power
- ◇.Ultra-deep tread depth,prick resistant design,suitable for all bad low-speed & short-distance transport conditions

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11.00R20	8.00	18PR	152/149	K	18.5	3550/3250	930
12.00R20	8.50	20PR	156/153	G	19.5	4000/3650	900



BYD887



- ◇.Rough pattern design,offer strong traction and self-cleaning ability
- ◇.The deepen pattern make the tyres have long mileage,fit for the short distance transportation and low speed on bad road condition
- ◇.Especially in the high temperature season,it can not use on the vehicles overpass the vehicles overpass the speed of 100km

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11.00R20	8.00	18PR	152/149	G	22.5	3550/3250	930
12.00R20	8.50	20PR	156/153	G	24.5	4000/3650	900



BYD988



- ◇.Suitable for highway and good road
- ◇.Steer wheel for bus and trailer

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12R22.5	9.00	18PR	152/149	K	19.5	3550/3250	930